

GT-40 Data Sheet

The GT-40 gamma ray spectrometer is a versatile tool which incorporates specific features which enable it to be used as part of field surveys and follow up laboratory measurements.



Left: GT40S with 104cm³ BGO detector. Right: GT40 with 345cm³ NaI detector. Image courtesy of Georadis.

The 8GB memory permits the calibration spectra to be stored to memory, meaning the operator can apply any standard coefficients and the instrument will calibrate itself. Calibrations can be defined for elements or compounds. By having the full calibration spectra stored to memory it is possible to isolate components within a compound, for instance the ratio of U:Ra. Up to 6 different calibration routines can be stored to memory and any user defined SI unit can be specified.

The GT-40 includes the ability to implement a local background reading for isolating counts from a particular sample. This function can be enhanced by fitting the Pb collimator (GT40S Shielded) which makes the system ideal for laboratory use. A laboratory stand will be available shortly which houses the instrument to improve measurement repeatability.

The Pb collimator can be removed with easy for use survey mode. A built in GPS module allows the operator to integrate geospatial positions without the inconvenience of a second instrument. Field observations can be recorded and stored along with each measurement using the inbuilt voice recorder.

Inbuilt Wifi enables the GT-40 to be controlled remotely using the freely available GeoMon software. The Wifi also enables Georadis to service the instrument remotely.

The instrument can be fitted with a 104cm³ BGO detector or a 104cm³ NaI detector. An optional 345cm³ NaI detector can also be supplied but the Pb collimator is not available with this particular detector.

Applications

- Exploration for Uranium, Thorium and other associated REEs.
- Geophysical Research.
- Geological Mapping.
- Baseline surveying.
- Core logging.
- Classification of building material.
- Radon risk assessment.
- Environmental monitoring.
- Surface Contamination surveys.
- Monitoring waste disposal sites

Product Dimensions

Physical	Dimensions (L x W x H)	Weight
(instrument only)	12cm x 12cm x 33.5cm	9kg

Technical Specifications

Detectors::	GT-40: NaI(Tl 76 x 76 mm, 345 cm ³ , with bi-alkali PMT. GT-40: S BGO or NaI, 51 x 51 mm, 104 cm ³ ,with bi-alkali PMT, Shielded with 25 mm lead.
Memory:	Minimum of 2000 survey stations with full 1024 channel spectrum, position and voice recording.
Control:	5 button control
Data Input/Output:	USB and Bluetooth.
Power Supply:	Rechargeable Li-Ion rechargeable battery For up to 10hours operation.
Operating Temperature:	-10 °C to +50 °C
Internal GPS Accuracy:	2.0m

Internal GPS Receiver Satellite SBAS (WAAS, EGNOS, MSAS)
Accessibility:

Gallery



The rear face of the GT40 houses the DC recharging jack and mini USB PC interface connector.



GT40 offers a simple GUI and daylight visible screen.



The GT40 Laboratory stand with Lead shielding and sample chamber.



GT40 carry harness





The GT40S Lead collimator is used to improve the directionality of records when taking spot measurement, but can be removed for regional mapping.

The GT40 carry harness permits real time background counts to be measured and referenced with SBAS GPS positions. the audio output on the GT40 will then alert the operator of areas which need further investigation.



The GT-40 can be used as a sensitive gamma ray scintilometer accompanied with gamma spectrometer function

working on backstage. The survey mode is rated for fast and easy sources targeting or as a stationary monitor of radioactivity.